



## Polar

High performance resin body and diffuser: resistant to corrosion caused by both atmospheric agents and chemical fertilizers, colors stabilized during UV rays treatment, thermal shock resistance from -60° to +90°C.

IP66	IP66
0,800 Kg / 0,0106 m <sup>3</sup> E27 max 1x23W	0,800 Kg / 0,0106 m <sup>3</sup> E27 max 1x23W
096667 White 096674 Black	096681 White 096698 Black
4000 K 1000 lm	4000 K 1000 lm
151991	151991



## Cometa

Die-cast aluminum body, anthracite or black powder coated finish. White PVC diffuser. The direct exposure to sun rays is not recommended.

IP54	IP54
1,500 Kg / 0,0124 m <sup>3</sup> E14 max 3 x 28W	1,500 Kg / 0,0124 m <sup>3</sup> E14 max 3 x 28W
082240 Anthracit. 082271 Black	082240 Anthracit. 082271 Black
3000 K 420 lm	3000 K 420 lm
101217	101217

## Medea

High performance resin body and diffuser: resistant to corrosion caused by both atmospheric agents and chemical fertilizers, colors stabilized during UV rays treatment, thermal shock resistance from -60° to +90°C.

IP66	IP66
0,800 Kg / 0,0109 m <sup>3</sup> E27 max 1x23W	0,800 Kg / 0,0109 m <sup>3</sup> E27 max 1x23W
096711 White 096704 Black	096735 White 096728 Black
4000 K 1000 lm	4000 K 1000 lm
151991	151991

