


Polar

High performance resin body and diffuser: resistant to corrosion caused by both atmospheric agents and chemical fertilizers, colors stabilized during UV rays treatment, thermal shock resistance from -60° to +90°C.




IP66

0,800 Kg / 0,0106 m³
E27 max 1 x 23W

096667 White
096674 Black

4000 K
1000 lm

151991



IP66

0,800 Kg / 0,0106 m³
E27 max 1 x 23W

096681 White
096698 Black


4000 K
1000 lm

151991



Medea

High performance resin body and diffuser: resistant to corrosion caused by both atmospheric agents and chemical fertilizers, colors stabilized during UV rays treatment, thermal shock resistance from -60° to +90°C.




IP66

0,800 Kg / 0,0109 m³
E27 max 1 x 23W

096711 White
096704 Black

4000 K
1000 lm

151991



IP66

0,800 Kg / 0,0109 m³
E27 max 1 x 23W

096735 White
096728 Black

4000 K
1000 lm

151991





Cometa


Die-cast aluminum body, anthracite or black powder coated finish. White PVC diffuser. The direct exposure to sun rays is not recommended.



082240



082271



IP54

1,500 Kg / 0,0124 m³
E14 max 3 x 28W

082240 Anthracit.
082271 Black

3000 K
420 lm

101217