















Park

















Recessed spotlight. PVC external body. Aluminum reflecting parabola. Glazed steel glass-setting frame. Clear glass.

		
150	120	120
		
190	133	120
105	75	83
 IP54	 IP67	 IP54
1,210 Kg / 0,0066 m ³ E27 max 1x 60W	0,580 Kg / 0,0032 m ³ GU10 max 1x 20W	0,900 Kg / 0,0032 m ³ G9 max 1x 15W
032825 Steel	032832 Steel	117881 Steel
 4000 K 980 lm	 4000 K 430 lm	 4000 K 530 lm
153964	253497	307879

Gravity

High performance resin body: resistant to corrosion caused by both atmospheric agents and chemical fertilizers, colors stabilized during UV rays treatment, thermal shock resistance from -60° to +90°C. Resistant to 5000 kg impact.

LED Bulbs LED GU10 3,5W and LED GX53 10W included. Settable CCT.

			
155	90	155	90
			
111	132	111	132
145	85	145	85
 IP67	 IP67	 IP67	 IP67
0,670 Kg / 0,0043 m ³ GX53 max 1x 10W	0,270 Kg / 0,0019 m ³ GU10 max 1x 6W	0,700 Kg / 0,0043 m ³ GX53 max 1x 10W	0,270 Kg / 0,0019 m ³ GU10 max 1x 6W
120324 Black	120249 Black	120386 Black	120317 Black
 4000 K 1000 lm	 4000 K 430 lm	 4000 K 1000 lm	 4000 K 430 lm
154008	253497	154008	253497