

SOFT CEILING LED 60X6 7527





painted aluminum, plastic PMMA

SOFT CEILING LED 90X6 7533

95 cm

7546 7533

SOFT CEILING LED 90X6

1xLED TUBE T8, max 16W, included

painted aluminum, plastic PMMA


7540 7527

SOFT CEILING LED 60X6

IxLED TUBE T8, max 11W, included







SOFT CEILING LED 60X20 7526


















SOFT CEILING LED 90X20 7531

93.5 cm


















20 cm















SOFT WALL LED 90X6 7534





6 cm

SOFT CEILING LED 120X6 painted aluminum, plastic PMMA

|--|

1xLED TUBE T8, max 22W, included



SOFT CEILING LED 90X20

2xLED TUBE T8, max 16W, included

painted aluminum, plastic PMMA

7542 7531

63 cm 63 cm

> SOFT CEILING LED 60X60 painted aluminum, plastic PMMA





Name	Size	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Power factor	Lifetime	Material
LED TUBE T8	60 cm	11W LED	3000K	1700 lm	120°	≥80	~220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS
LED TUBE T8	90 cm	16W LED	3000K	2300 lm	120°	≥80	~220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS
LED TUBE T8	120 cm	22W LED	3000K	3200 lm	120°	≥80	~220-230 V, 50/60 Hz	>0,5	30000h	CLEAR GLASS

WHITE P004 RAL 9003 GRAPHITE P010 RAL 7016

SOFT WALL LED 60X6 painted aluminum, plastic PMMA

7541 7528

1xLED TUBE T8, max 11W, included



SOFT WALL LED 90X6

painted aluminum, plastic PMMA

7548 7534

1xLED TUBE T8, max 16W, included

Nowodvorski

COLLECTIONS