


Fluo Bi-Emission*



LED SMD SAMSUNG
Up-light included - Driver TRIDONIC ON/OFF included


Power	Beam	Lumen	CCT	Finish	Code
27 W	105°	3250 lm	3000 K	White	192666
				Black	192710
		4050 lm	4000 K	White	192741
				Black	192758

UP-LIGHT INFO

Power	Beam	Lumen	CCT
13 W	105°	1750 lm	3000 K
		2050 lm	4000 K

KIT DIMMABLE DRIVER*

Code
1-10V 270692
DALI/Push 270876



LED SMD SAMSUNG
Up-light included - Driver TRIDONIC ON/OFF included

Power	Beam	Lumen	CCT	Finish	Code
36 W	105°	5050 lm	3000 K	White	192703
				Black	192697
		5350 lm	4000 K	White	192673
				Black	192642


UP-LIGHT INFO

Power	Beam	Lumen	CCT
18 W	105°	2550 lm	3000 K
		2800 lm	4000 K

KIT DIMMABLE DRIVER*

Code
1-10V 270883
DALI/Push 270937

Light beam: BI-EMISSION
WIDE




MOUNTING KIT Required - Page 641


* Separate switching on of direct and indirect output (available only for on-off versions). Control of the direct and indirect output in synchrony (versions with 1-10V and Push dimming). The dimmable power supplies must be ordered in concomitance with the product and will be included inside the fittings by replacing the on-off power supply. The linear connection is available only for the on-off versions of the products.



Fluo Bi-Emission 1200



Fluo Bi-Emission 1800



The single final cup is 2.5 mm width.