


Basic Wide




① 90 mm

0,370 Kg/0,0017 m³

LED SMD SAMSUNG Driver PHILIPS ON/OFF included

Power	Beam	Lumen	CCT	Finish	Code
10 W	85°	1150 lm	3000 K	White	193519
		1200 lm	4000 K	White	193403




① 125 mm

0,630 Kg/0,0027 m³

LED SMD SAMSUNG Driver PHILIPS ON/OFF included

Power	Beam	Lumen	CCT	Finish	Code
15 W	87°	1750 lm	3000 K	White	193526
		1800 lm	4000 K	White	193410
20 W		2400 lm	3000 K	White	193533
		2500 lm	4000 K	White	193427



① 160 mm

1,130 Kg/0,0056 m³

LED SMD SAMSUNG Driver PHILIPS ON/OFF included


Power	Beam	Lumen	CCT	Finish	Code
30 W	90°	3050 lm	3000 K	White	193540
		3150 lm	4000 K	White	193434

DIMMABLE DRIVER* Optional

Model	Control	Power	Output	Measure (LxHxW)	Code
Basic 10 W	1-10V	12 W	300 mA	150 x 29 x 43 mm	218823
	DALI/Push	10 W	300 mA	130 x 30 x 43 mm	220772
Basic 15 W	1-10V	15 W	450 mA	150 x 29 x 43 mm	218830
	DALI/Push	17 W	450 mA	130 x 30 x 43 mm	220796
Basic 20 W	DALI/Push	25 W	700 mA	130 x 30 x 43 mm	220789
Basic 30 W	1-10V	31 W	900 mA	150 x 29 x 43 mm	218854
	DALI/Push	45 W	900 mA	150 x 30 x 43 mm	220802




Light beam: WIDE



m	lx	øm
1	188	1,84
2	47	3,69
3	20	5,54
4	11	7,39
5	7	9,24




CRI≥80 10W 85° 1150lm 3000K



m	lx	øm
1	318	1,72
2	79	3,44
3	35	5,17
4	19	6,89
5	12	8,61



CRI≥80 15W 87° 1750lm 3000K



m	lx	øm
1	591	1,84
2	147	3,69
3	65	5,53
4	36	7,38
5	23	9,23



CRI≥80 30W 90° 3050lm 3000K

* The dimmable power supplies must be ordered in concomitance with the product and will be included inside the fittings by replacing the on-off power supply.

