



Lika Trim



68 x 37 mm
0,130 Kg/0,0005 m³

LED COB OSRAM Driver ON/OFF included


Power	Beam	Lumen	CCT	Finish	Code
6 W	29°	480 lm	3000 K	Black	+ ■ 206196
		520 lm	4000 K	Black	+ ■ 267869



140 x 37 mm
0,320 Kg/0,0013 m³

LED COB OSRAM Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish	Code
12 W	29°	1200 lm	3000 K	Black	+ ■ 206219
		1250 lm	4000 K	Black	+ ■ 267876



273 x 37 mm
0,480 Kg/0,0016 m³

LED COB OSRAM Driver ON/OFF included


Power	Beam	Lumen	CCT	Finish	Code
20 W	29°	1750 lm	3000 K	Black	+ ■ 206233
		1850 lm	4000 K	Black	+ ■ 267883

DIMMABLE DRIVER* Optional

Model	Control	Power	Output	Measure (LxHxW)	Code
Lika 6 W	DALI	10 W	700 mA	132x20x30 mm	267982
Lika 12 W	DALI	12 W	700 mA	135x24x72 mm	267999
Lika 20 W	DALI/Push	25 W	600 mA	135x24x72 mm	268002



Light beam: ACCENT



CRI≥90 12W 29° 1200lm 3000K

* The dimmable power supplies must be ordered in concomitance with the product and will be included inside the fittings by replacing the on-off power supply.

