
Lika Trimless






75 x 70 mm
0,220 Kg/0,0006 m³

LED COB OSRAM Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish		Code
6 W	29°	480 lm	3000 K	Black	■	206202
		520 lm	4000 K	Black	■	267890






145 x 70 mm
0,390 Kg/0,0013 m³

LED COB OSRAM Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish		Code
12 W	29°	1200 lm	3000 K	Black	■	206226
		1250 lm	4000 K	Black	■	267906





278 x 70 mm
0,720 Kg/0,0023 m³

LED COB OSRAM Driver ON/OFF included


Power	Beam	Lumen	CCT	Finish		Code
20 W	29°	1750 lm	3000 K	Black	■	206240
		1850 lm	4000 K	Black	■	267913

DIMMABLE DRIVER* Optional

Model	Control	Power	Output	Measure (L x H x W)	Code
Lika 6 W	DALI	10 W	700 mA	132 x 20 x 30 mm	267982
Lika 12 W	DALI	12 W	700 mA	135 x 24 x 72 mm	267999
Lika 20 W	DALI/Push	25 W	600 mA	135 x 24 x 72 mm	268002



Light beam: ACCENT



m	lx	cm
1	2786	0,58
2	696	1,16
3	309	1,74
4	174	2,32
5	111	2,90



CRI≥90 12W 29° 1200lm 3000K

* The dimmable power supplies must be ordered in concomitance with the product and will be included inside the fittings by replacing the on-off power supply.





