

Halo

Ceiling lamp with circular base and powder coated aluminum body. Opal polycarbonate diffuser. Available with three different diameters in white color. Light source with integrated LED, starting binning ≤ 2-Step MacAdam; available with 3000 K and 4000 K color temperature; CRI ≥ 80; LED useful life 35.000; protection IP20, insulation class I.



Up-light included.

Source	LED SMD	Insulation class	I
Power	26W / 32W / 46W	IP	20
Driver included	On/Off	Material	Aluminum
Drivers available	No		
CCT	3000 K / 4000 K		
CRI	≥80		
LED life	35.000 h		



LED SMD Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish	Code
26 W	110°	3150 lm	3000 K	White	223186
		3450 lm	4000 K	White	223193

2,750 Kg/0,0177 m³



LED SMD Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish	Code
32 W	110°	4050 lm	3000 K	White	223209
		4200 lm	4000 K	White	223216

4,430 Kg/0,0313 m³



LED SMD Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish	Code
46 W	110°	5950 lm	3000 K	White	223223
		6250 lm	4000 K	White	223230

6,600 Kg/0,0566 m³

KIT PENDANT

Required	Finish	Code
No	White	223247

