


Oracle Slim Round

Suspended lamp consisting of a thin matt white or black painted aluminum frame and opal polycarbonate diffuser. Available in four different sizes. Integrated LEDs; available in 3000 K and 4000 K color temperatures and ON-OFF or DALI/Push control; CRI ≥ 80; LED useful life 20.000 h ; IP20 protection, insulation class II.

Source	LED SMD	LED life	20.000 h
Power	32W / 89W	Insulation class	II
Driver included	On/Off / DALI/Push	IP	20
Drivers available	No	Material	Aluminum
Beam	115°		
CCT	3000 K / 4000 K		
CRI	≥80		



LED SMD Driver included

Measure	Weight	Volume	Power	Driver	Lumen	CCT	Finish		Code	
ø 500	1,400 Kg	0,0376 m³	32 W	On-Off	3150 lm	3000 K	White		229461	
						3000 K	Black		229492	
						3350 lm	4000 K	White		269856
						4000 K	Black		304380	
	1,100 Kg	0,0272 m³	29 W	DALI/Push	3000 lm	3000 K	White		304373	
						3000 K	Black		304366	
ø 700	1,660 Kg	0,0809 m³	38 W	On-Off	4300 lm	3000 K	White		229485	
						3000 K	Black		229515	
						4500 lm	4000 K	White		269863
						4000 K	Black		304410	
	1,200 Kg	0,0534 m³	39 W	DALI/Push	4150 lm	3000 K	White		304403	
						3000 K	Black		304397	
	ø 900	1,800 Kg	0,2212 m³	55 W	On-Off	5400 lm	3000 K	White		229478
							3000 K	Black		229508
5700 lm							4000 K	White		269870
4000 K							Black		304441	
1,500 Kg		0,0857 m³	43 W	DALI/Push	4600 lm	3000 K	White		304434	
						3000 K	Black		304427	
ø 1500	2,480 Kg	0,3072 m³	89 W	On-Off	9000 lm	3000 K	White		265957	
						3000 K	Black		285061	
						9650 lm	4000 K	White		285078
						4000 K	Black		304472	
	2,000 Kg	0,3072 m³	76 W	DALI/Push	7050 lm	3000 K	White		304465	
						3000 K	Black		304458	

Cable length 2500 mm

