
Linus

Linear aluminum lamp with direct and indirect light. The lamp is modular and can be used individually or in a continuous line. Integrated LED, starting binning ≤ 3-Step MacAdam; CRI ≥ 80; protection IP20, insutlation class I. Dimmable power supply 1-10V integrated as standard.

Source	LED SMD	**LED life**	50.000 h
Power	32W	**Insulation class**	I
Driver included	1-10V	**IP**	20
Drivers available	No	**Material**	Aluminum
MacAdam	SDCM 3	**Warranty**	5 years
CCT	3000 K / 4000 K		
CRI	≥80		





2,550 Kg/0,0158 m³

Cable length 1500 mm


LED SMD **Up-light included - Driver 1-10V included**


Power	Beam	Lumen	CCT	Finish		Code
32 W	104°	3450 lm	3000 K	White		241968
				Black	■	241975
		3600 lm	4000 K	White		268231
				Black	■	268217

UP-LIGHT INFO

Power	Beam	Lumen	CCT
32 W	104°	3450 lm	3000 K
		3600 lm	4000 K

CORNER Optional - Up-light not included





0,260 Kg/0,0023 m³

Power	Beam	Lumen	CCT	Finish		Code
4 W	104°	430 lm	3000 K	White		241999
				Black	■	242002
		450 lm	4000 K	White		268149
				Black	■	268118




STRUCTURE CONNECTOR

Required	Code
Yes - 1 Kit x connection	241982



Light beam: BI-EMISSION WIDE



m	lx	em
1	572	2,56
2	143	5,12
3	64	7,68
4	36	10,24
5	23	12,80



CRI≥83 32+32W 104°+104° 3600+3600lm 4000K

P. 387

