


Universal Square new

Diffusive ceiling lamp for indoor ceiling or wall installation, suitable for general and uniform lighting. Varnished steel body with white finish, plastic diffuser. Integrated LED source, available in 4 different powers. LED useful life 17.500 h; protection IP20, insulation class II.


Source	LED SMD	Insulation class	II
Power	13,5W / 36W	IP	20
Driver included	On/Off	Material	Steel
Drivers available	No		
CCT	3000 K / 4000 K		
CRI	≥80		
LED life	25.000 h		



LED SMD Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish		Code
13,5W	110°	1250 lm	3000 K	White		138633
			4000 K	White		321769


new



LED SMD Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish		Code
19 W	110°	1950 lm	3000 K	White		138640
			4000 K	White		321745


new



LED SMD Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish		Code
25 W	110°	2600 lm	3000 K	White		138657
			4000 K	White		321707

new



LED SMD Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish		Code
36 W	110°	4300 lm	3000 K	White		240374
			4000 K	White		321660

new

