


Universal Round new

Diffusive ceiling lamp for indoor ceiling or wall installation, suitable for general and uniform lighting. Varnished steel body with white finish, plastic diffuser. Integrated LED source, available in 4 different powers. LED useful life 17.500 h; protection IP20, insulation class II.


Source	LED SMD	Insulation class	II
Power	13,5W / 36W	IP	20
Driver included	On/Off	Material	Steel
Drivers available	No		
CCT	3000 K / 4000 K		
CRI	≥80		
LED life	25.000 h		



LED SMD Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish	Code
13,5W	110°	1250 lm	3000 K	White	138596
			4000 K	White	321776


new



LED SMD Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish	Code
19 W	110°	1950 lm	3000 K	White	138602
			4000 K	White	321752


new



LED SMD Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish	Code
25 W	110°	2600 lm	3000 K	White	138619
			4000 K	White	321738

new



LED SMD Driver ON/OFF included

Power	Beam	Lumen	CCT	Finish	Code
36 W	110°	4300 lm	3000 K	White	240367
			4000 K	White	321684

new

