

Thor new


Adjustable linear projector for surface installation with oblique light effect. Die-cast aluminum body, clear glass diffuser.

Integrated LED source, available in two lengths (500 mm and 1000 mm). Adjustability +/- 90° from the vertical, IP65 protection index, IK06 impact resistance, 3000 K or 4000 K color temperature, 24 Vdc power supply input; LED useful life 50.000 h. Optionally available with anti-glare visor.

PRO High-tech product with high quality materials, intended for professional use.

Source	LED SMD	LED life	50.000 h
Power	18W / 40W	Insulation class	III
Driver included	No	IP	65
Drivers available	On/Off	Material	Aluminum
MacAdam	SDCM 3		
CCT	3000 K / 4000 K		
CRI	≥80		


LED SMD OSRAM Driver not included



1,490 Kg/0,0057 m³
Cable length 500 mm

Power	Beam	Lumen	CCT	Finish	Code	
20 W	28°	2300 lm	3000 K	White	318523	new
				Anthracite	261331	
		2450 lm	4000 K	White	322148	new
				Anthracite	322131	new

LED SMD OSRAM Driver not included



2,460 Kg/0,0108 m³
Cable length 500 mm

Power	Beam	Lumen	CCT	Finish	Code	
40 W	28°	4500 lm	3000 K	White	322117	new
				Anthracite	261355	
		4950 lm	4000 K	White	322049	new
				Anthracite	322018	new

OPTIONAL Not included



		Power	Finish	Code	
Visor	18W	White	318516	new	
		Anthracite	261362		
	40W	White	322162	new	
		Anthracite	261379		

ON/OFF DRIVER Not included/Required

Power	Output	Measure	Code
40 W	24 Vdc	171 x 37 x 61 mm	272108
100 W	24 Vdc	220 x 39 x 68 mm	226200
185 W	24 Vdc	220 x 39 x 68 mm	226217

