


Motion Sensor Activation
 Max. distance 5M. Temperature less than 20°C.
 The lights need to be installed at least
 1.5-2.5M from the ground.




LOVETO - 9120622

Dimmable
 Anthracite Die-Casting
 Aluminium & Acrylic Diffuser
 LED 1.5 Watt 136Lm 3000K
 3.7 Volt Beam Angle 125° IP65
 Solar / Switch On/Off
 L: 14.5 W: 14.5 H: 50 cm




LOVETO - 9120621

Dimmable
 Anthracite Die-Casting
 Aluminium & Acrylic Diffuser
 LED 1.5 Watt 90Lm 3000K
 3.7 Volt Beam Angle 125° IP65
 Solar / Switch On/Off
 L: 14.5 W: 16.2 H: 24 cm




BAY - 9120711

Dimmable
 Anthracite Die-Casting Aluminium
 Clear Glass & Acrylic Diffuser
 LED 1.5 Watt 82.67Lm 3000K
 3.7 Volt Beam Angle 87° IP65
 Solar / Switch On/Off
 L: 12.6 W: 8.3 H: 25.2 cm



DYN - 9190101

Dimmable
 Anthracite Die-Casting
 Aluminium & Acrylic Diffuser
 LED 1.5 Watt 199.47Lm 3000K
 3.7 Volt Beam Angle 110° IP65
 Solar / Switch On/Off
 L: 16 W: 11.5 H: 6 cm



IP65

