

Line

B W MG

IP20 LED

EN Fittings material— aluminum, shades – white, black, matte gold. Integrated LED sources, acrylic diffuser. Color temperature is from 3000K to 4000K. Trendy asymmetry in design. Adjustable height.

DE Material der Beschläge: Aluminium, Farbtöne: Weiß, Schwarz, mattes Gold. Integrierte LED-Quellen, Acryl-Diffusor. Farbtemperatur von 3000K bis 4000K. Trendige Asymmetrie im Design. Einstellbare Höhe.

IT Materiale dell'armatura - alluminio, tonalità - bianco, nero, oro opaco. Sorgenti LED integrate, diffusore in acrilico. Temperatura di colore da 3000K a 4000K. Asimmetria alla moda nel design. Altezza regolabile.

FR Matériau de l'armature : aluminium, teintes : blanc, noir, dorée mat. Sources LED intégrées, diffuseur acrylique. Température de couleur : de 3 000 K à 4 000 K. Design asymétrique tendance. Hauteur réglable.



1 ■ ■ ■



2 ■




3 ■




4 ■

- 1 ■ **MOD016PL-L75B** 2 ■ **MOD016PL-L75MG4K** 3 ■ **MOD054PL-L52B3K** 4 ■ **MOD054PL-L52B4K**
- **MOD016PL-L75W**
- **MOD016PL-L75MG3K**


LED 79W 3100lm
t° 3000K >82Ra 120°
IP 20




LED 75W 3500lm
t° 4000K >80Ra 120°
IP 20



LED 52W 2000lm
t° 3000K >80Ra 60°
IP 20



LED 52W 2200lm
t° 4000K >80Ra 60°
IP 20



MOD016PL-L75MG3K